DID YOU KNOW?

about our...



PRODUCT

Internal Threaded Stud Anchor

INTERNAL THREADED STUD ANCHOR CARBON STEEL / ZINC PLATED (ROHS COMPLIANT) / CLASS 5.8 AS4291.1

Part	Qfind	Size	Length	Drill Hole Size ø	Internal Thread Length	Inner ø	Outer ø	Pack Qty
			L (mm)	D (mm)	TL (mm)	D _i (mm)	D _o (mm)	
MCIMSZDM080090	MCI100	M8 x 1.25	90	14	30	8	12	25
MCIMSZDM100090	MCI101	M10 x 1.50	90	18	35	10	16	25
MCIMSZDM120090	MCI102	M12 x 1.75	90	22	40	12	20	10
MCIMSZDM120125	MCI103	M12 x 1.75	125	22	40	12	20	10
MCIMSZDM160125	MCI104	M16 x 2.00	125	28	40	16	25	10
MCIMSZDM200180	MCI105	M20 x 2.50	180	34	60	20	30	5


APPLICATIONS

- · Fixing to concrete or masonry substrates
- · Temporary fixings/removable applications
- · Applications that require non-expansion type fasteners
- · Applications that require closer edge distance and spacing

FEATURES

- · Flush setting
- Non-expanding anchor
- · No expansion forces on the concrete
- Eliminates risk of concrete blow out
- Can be installed close to edge
- Reduced spacing between anchors







Disclaimer: While every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees, disclaim any and all liability to any person in respect of anything or the consequences of anything done or omitted to be done in reliance upon the whole or any part of this document.

ENGINEERING