

DID YOU KNOW?



about our... **Lifting Eye Bolt and Nut**

Bolt and nut are both approved and certified for lifting.

Can be used in axial  or angular  loading.

LIFTING EYE BOLT ZINC YELLOW PASSIVATE / DIN 580 / GRADE C15E

Part	QFind	Size	Height of eye (mm)	Length of thread (mm)	Pack Qty
ULEBC5YD5M08	EBCYM8	M8	36.0	13.0	100
ULEBC5YD5M10	EBCYM10	M10	45.0	17.0	50
ULEBC5YD5M12	EBCYM12	M12	53.0	20.5	50
ULEBC5YD5M16	EBCYM16	M16	62.0	27.0	25
ULEBC5YD5M20	EBCYM20	M20	71.0	30.0	10
ULEBC5YD5M24	EBCYM24	M24	90.0	36.0	5



▶ MARKINGS:

- CE (European Conformity)
- WLL (Working Load Limit)

LIFTING EYE NUT ZINC YELLOW PASSIVATE / DIN 582 / GRADE C15E

Part	QFind	Size	Height of eye (mm)	Collar thickness (mm)	Pack Qty
ULENC5YD5M08	ENCYM8	M8	36.0	8.5	100
ULENC5YD5M10	ENCYM10	M10	45.0	10.0	50
ULENC5YD5M12	ENCYM12	M12	53.0	11.0	50
ULENC5YD5M16	ENCYM16	M16	62.0	13.0	25
ULENC5YD5M20	ENCYM20	M20	71.0	16.0	10
ULENC5YD5M24	ENCYM24	M24	90.0	20.0	5



▶ MARKINGS:

- CE (European Conformity)
- WLL (Working Load Limit)

Features

- Approved for lifting.
- Stamped with working load for axial loading.

Applications

- Connection point for: Anchoring, rigging, pulling, lifting or hoisting.
- Can be used with: rope, cables, shackles and hooks.
- Threaded into steel: equipment, machine and structures.
- Bolted through steel or timber profiles and secured with a nut.



DOWNLOAD:

These products have a **Test Certificate** online.

ONLINE

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

hobson.com.au **QUALITY FASTENERS SINCE 1935**

